



UL VERIFICATION SERVICES INC.

HARDLINES TESTING LABORATORY • 611 DREAM VALLEY ROAD • ROGERS, AR 72756
PHONE: (479) 636-8782 • FAX: (479) 636-8961 • ROG.Hardlines.Customer.Service@crs.ul.com

Evaluation of Test Results

Lab Report No: ARHL1028194

Issue Date: August 14, 2023



Item Description: Jla Mp-Galen Roman Shade

Rating: **Pass**

CLIENT: E&E Co Ltd

BUYER: Supplier Testing

DEPARTMENT: 00

BRAND: Madison Park (National)

ORDER TYPE: Domestic

SOURCING OFFICE: Not Applicable

TEST TYPE: Supplier Only-Limited Testing

VENDOR STOCK NUMBER: MP40-6547

REASON FOR TESTING: Evaluation of the sample per client requirements.

COUNTRY OF ORIGIN: China

SUPPLIER NAME: E&E Co Ltd

HOST VENDOR NUMBER: 444096

SUPPLIER ID: 28009219

FACTORY NAME: Not Applicable

FACTORY NUMBER: Not Applicable

CHILDREN'S PRODUCT: No

*** Please see the following pages for additional item information ***

This letter / report / certificate shall not be reproduced (except in full version) without the written approval of the UL Company. ("UL")

LETTERS / REPORTS / CERTIFICATES: Letters / Reports / Certificates of UL are issued for the exclusive use of the Customer to whom they are addressed. No quotation from reports / certificates or use of the UL's name is permitted except by UL's express written authorization. Letters / reports / certificates apply only to the specific materials, products or processes tested, examined or surveyed and are not necessarily indicative of the qualities of apparently identical or similar materials, products or processes. Reports / Certificates of UL do not relieve sellers / suppliers from their contractual responsibilities with regard to the quality / quantity of the goods in delivery nor do they prejudice the Customer's right to claim against sellers / suppliers for compensation for any apparent and/or hidden defects not detected during UL's random inspection or testing or audit. The liability of UL to the Customer in contract, tort (including negligence or breach of statutory duty) or howsoever, and whatever the cause thereof, (a) for any loss of profit, business, contracts, revenues, or anticipating savings; or (b) for any special indirect or consequential damage of any nature whatsoever, shall be limited to the amount of the fee paid in respect of the specific Work(s) which give rise to such claim.

For Reports / Certificates, refer to the UL VS Terms and Conditions.

Decision Rule: the declaration of conformity is given not taking into account the measurement uncertainty.

Level of risk associated with the Decision Rule: The results issue by UL Solutions does not take in consideration the measurement uncertainty, but when the value is close to the limit, the test, if repeated by another laboratory,

ADDITIONAL SAMPLE INFORMATION

SIZE(S)	COLOR(S)
27"W x 64"L	Not Applicable
PO NUMBER(S)	
Not Applicable	
UPC CODE(S)	
Not Applicable	
ITEM NUMBER(S)	
Not Applicable	
APPLICATION ID	
6087659	

UL VERIFICATION SERVICES INC.



Andrea Bertschy
LABORATORY MANAGER

UL VERIFICATION SERVICES INC.



Daniel Sabou
SENIOR LABORATORY MANAGER

This letter / report / certificate shall not be reproduced (except in full version) without the written approval of the UL Company. ("UL")

LETTERS / REPORTS / CERTIFICATES: Letters / Reports / Certificates of UL are issued for the exclusive use of the Customer to whom they are addressed. No quotation from reports / certificates or use of the UL's name is permitted except by UL's express written authorization. Letters / reports / certificates apply only to the specific materials, products or processes tested, examined or surveyed and are not necessarily indicative of the qualities of apparently identical or similar materials, products or processes. Reports / Certificates of UL do not relieve sellers / suppliers from their contractual responsibilities with regard to the quality / quantity of the goods in delivery nor do they prejudice the Customer's right to claim against sellers / suppliers for compensation for any apparent and/or hidden defects not detected during UL's random inspection or testing or audit. The liability of UL to the Customer in contract, tort (including negligence or breach of statutory duty) or howsoever, and whatever the cause thereof, (a) for any loss of profit, business, contracts, revenues, or anticipating savings; or (b) for any special indirect or consequential damage of any nature whatsoever, shall be limited to the amount of the fee paid in respect of the specific Work(s) which give rise to such claim.

For Reports / Certificates, refer to the UL VS Terms and Conditions.

Decision Rule: the declaration of conformity is given not taking into account the measurement uncertainty.
Level of risk associated with the Decision Rule: The results issue by UL Solutions does not take in consideration the measurement uncertainty, but when the value is close to the limit, the test, if repeated by another laboratory,



Installation Instructions

Shade Size	Shade (A)	Bracket (B)	Bracket Screws (C)	Wall Anchors (D)
23in. x 84in.	1	2	4	4
27in. x 84in.	1	2	4	4
29in. x 84in.	1	2	4	4
31in. x 84in.	1	2	4	4
33in. x 84in.	1	2	4	4
34in. x 84in.	1	2	4	4
35in. x 84in.	1	2	4	4
36in. x 84in.	1	2	4	4

Step 1 – Checklist
You will need the following tools:
- Drill
- Pencil
- Step Ladder
- Measuring Tape
- Screwdriver

Step 2 – Mounting Brackets
The Roman Shade can be mounted to either the wall (Wall Mount) or Outside the Window Frame (using the provided Bracket B). You will need to leave 2 inches of space from the side of the window to properly mount the Bracket B. Check for the Headrail (H) if you are mounting the Bracket on the wall.

Mounting Outside the Window Frame (Wall)
Fix the Bracket (B) on the wall inside and above the window frame. Ensure that the Bracket is mounted in 3-5 inches from the side of the window frame. Then place the Bracket Screws (C) through holes on the back side of the shade and tighten until securely fastened to the wall.

Mounting inside the Window Frame (Ceiling)
Fix the Bracket (B) on the ceiling that is inside the window frame, leaving a space of 2 inches or more from the window. Ensure that the Bracket is mounted in 3-5 inches from the side of the window frame. Then place the Bracket Screws (C) through the top holes and tighten until securely fastened to the top of the window frame.

Step 3 – Fitting the Shade & Securing the Headrail
For easier fitting, remove the Roman Shade (A) from the hook and loop fastener on the front of the Headrail (H).
Place the Headrail (H) over the Bracket (B) by inserting the back side of the Headrail (H) on first and then pushing the front side toward the shade. The shade will fit snugly in place. Then check for the correct fit when the Headrail (H) is secured.
Once correctly mounted to a Bracket, Shade (A) fits the hook and loop fastener on the front of the Headrail (H).

Step 4 – Operation of Your shade
To lower the shade:
Pull the handle on the back to lower down the shade until the desired height. Pull the handle again to hold the shade in place.
To raise the shade:
Push the handle on the back to raise the shade until the desired height. Push the handle again to hold the shade in place.

Step 5 – Maintaining Your Shade
Dust your shade with a soft cloth, cloth or a feather duster. Lower the shade to its fullest length for a complete cleaning. You can also remove the shade from the bar, with the hook and loop fastener and lightly shake for a simple cleaning.

FABRIC WEIGHT

TEST CONDUCTED	Actual Weight (oz/yd ²)	Actual Weight (g/m ²)	Specified Weight oz/yd ² (single value or range)	Specified Weight g/m ² (single value or range)	RATING
<i>FABRIC WEIGHT - ASTM D 3776 meets specified weight or weight range</i>					
Roman Shade - White	6.34	214.96	---	---	---

MEASUREMENT - MISCELLANEOUS						
#1		COLOR: Roman Shade - White			SIZE: 27"W x 64"L	
Tolerance (in.) - +	Component Description	Measurement Location	Labeled (in.)	Actual Flat / Circ. (in.)	Difference + / - (in.)	RATING
-1 1	roman shade	Length	64.000	64.000	0.000	P
-1 1	roman shade	Width	27.000	27.125	0.125	P