

# N A T O R I

## Purchase Order

PO NO: **PO010847**  
 Manual PO NO: **12622**  
 Date: 01/02/2025  
 Modified Date: 01/02/2025

TO:	SHIP TO:
E & E CO. , LTD. dba JLA HOME 45875 NORTHPORT LOOP EAST Fremont CA 94538 United States of America	The Natori Company, Inc. 5 Empire Blvd Carlstadt NJ 07072 United States of America

SHIP VIA:	PAYMENT TERMS:	ETD:	FOB:
BOAT	30 DAYS	05/01/2025	CHNPLANT

DESCRIPTION	CONTENT	US QUOTA CATEGORY	QUOTA HTS #
FWL 10 FROSTED FAUX FUR	BODY: 100% POLYESTER /TRIM:	650	6108.92.00.30

STYLE	COLOR	SIZE	DESCRIPTION	QTY	UOM	BODY TYPE	UNIT PRICE	EXT. PRICE
U74010	CAS	XS	Frosted Faux Fur Robe Length: 52"-CASHMERE-XS	138.00	PIECE	Robe Length:	14.50	2,001.00
U74010	CAS	S	Frosted Faux Fur Robe Length: 52"-CASHMERE-S	276.00	PIECE	Robe Length:	14.50	4,002.00
U74010	CAS	M	Frosted Faux Fur Robe Length: 52"-CASHMERE-M	288.00	PIECE	Robe Length:	14.50	4,176.00
U74010	CAS	L	Frosted Faux Fur Robe Length: 52"-CASHMERE-L	178.00	PIECE	Robe Length:	14.50	2,581.00
U74010	CAS	XL	Frosted Faux Fur Robe Length: 52"-CASHMERE-XL	120.00	PIECE	Robe Length:	14.50	1,740.00
<b>SubTotal</b>				<b>1,000.00</b>				

PO 12622

<b>TOTAL UNITS</b>	<b>1,000.00</b>	<b>TOTAL : USD</b>	<b>14,500.00</b>
--------------------	-----------------	--------------------	------------------

Disclaimer:  
 Send All Invoices to: NATORI 261 5th Avenue, Suite 2400, New York, NY 10016 Attention Accounts Payable (accounts.payable@natori.com)  
 Our purchase order number must be shown on all invoices, packages, bill of loading, statements, shipping notices, packing slips etc.  
 We reserve the right to cancel, return or refuse any or all goods not delivered as specified herein.  
 This purchase order is subject to the terms and conditions set forth on the face hereof and to any attachments, which are made and express part of this order.

PREPARED BY: Judi O'Donnell  
 FACTORY CONFIRMATION: \_\_\_\_\_

**The Natori Company, Inc.**

Confirmation sample approval needed before bulk is cut  
 Submit T.O.P at beginning of production  
 Please pack as per the instructions in the Natori Supplier Manual